

eni Dexron-VI ATF



Dexron-VI ATF is approved for use in all General Motors passenger cars, trucks and vans with automatic transmissions. Recommended for use where Dexron VI, Dexron III or Dexron III H specification is recommended.

Approval Number GM J-60306

TYPICAL CHARACTERISTICS

| PROPERTY | METHOD | DEXRON-VI ATF |
|----------------------|--------|---------------|
| Density, kg/l @ 15°C | D4052 | 0.846 |
| Color | - | Red |
| Flash Point, °C | D92 | 206 |
| Viscosity | | |
| cSt @ 40°C | D445 | 29.8 |
| cSt @ 100°C | D445 | 6.0 |
| Viscosity Index | D2270 | 151 |
| Pour Point, °C | D97 | -54 |
| Brookfield Viscosity | | |
| cP @ -20°C | D2983 | 1,053 |
| cP @ -30°C | D2983 | 3,164 |
| cP @ -40°C | D2983 | 12,030 |
| Sulphated Ash, % wt | D874 | 0.02 |
| Total Base No. | D2896 | 2.0 |

AVAILABLE PACKAGING: Bulk, Totes, Drums, Kegs, Pails, Cases

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.