

# eni i-Sint 4AM



i-Sint 4AM SAE 10W-30, 10W-40 and 20W-50 engine oils are engineered to meet the most demanding lubrication requirements of modern gasoline fueled engines. Formulated with advanced additives and premium quality base stocks, i-Sint 4AM oils protect engines against undesirable deposits, oxidation, viscosity and thermal breakdown.

## TYPICAL CHARACTERISTICS SAE GRADE

		10W-30	10W-40	20W-50
Viscosity @ 40 °C	cSt	70.5	104.1	175
Viscosity @ 100 °C	cSt	10.7	15.1	20.3
Viscosity Index		140	151	136
CCS Viscosity	cP	6300 @-25°C	6600 @-25°C	6600 @-15°C
Pour Point	°C	-36	-36	-27
Flash Point	°C	228	228	232
Evaporative Loss, NOACK, wt%		<15	<15	<15
Specific Gravity 15 °C		0.867	0.867	0.878
Zinc (ppm)		850	850	860
Phosphorus (ppm)		700	700	700

### Performance Levels:

- API SN
- ILSAC GF-5 (10W-30)

### AVAILABLE PACKAGING: Bulk, Totes, Drums, Pails, Cases

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.