

# eni i-Sint 4AM



i-Sint 4AM 5W-20 and 5W-30 are Synthetic Blend Passenger Car Engine Oils engineered to meet the most demanding lubrication requirements of modern gasoline fueled engines. Formulated with advanced additives and premium quality base stocks, i-Sint 4AM oils protect engines against undesirable deposits, oxidation, viscosity, and thermal breakdown. SAE 5W-20 and 5W-30 are Resource Conserving, meeting API service SN and ILSAC GF-5, as well as older categories: API SM, SL and previous ILSAC categories.

## TYPICAL CHARACTERISTICS

SAE GRADE	METHOD		5W-20	5W-30
Viscosity @ 40 °C	D445	cSt	49.7	61.6
Viscosity @ 100 °C	D445	cSt	8.6	10.4
Viscosity Index	D2270		150	158
CCS Viscosity	D5293	cP	6000 @-30°C	6200 @-30°C
Pour Point	D97	°C	-39	-39
Flash Point	D92	°C	216	220
Evaporative Loss, NOACK, wt%	D5800		<15	<15
Specific Gravity 15°C	D4052		0.862	0.861
Zinc (ppm)	D4951		850	850
Phosphorus (ppm)	D4951		700	700

### Performance Levels:

- API SN
- ILSAC GF-5
- Resource Conserving

### PACKAGING AVAILABLE: Bulk, Totes, Drums, Pails, Cases

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.