



# eni i-Sint Race 4AM

**i-Sint Race 4AM** is designed for use in high-performance, high horsepower competition engines. Formulated with superior heavy-duty additives, Group II base oils, and shear stable viscosity modifiers, **i-Sint Race 4AM** provides superior protection against wear and thermal breakdown under high loads and high operating temperatures experienced in racing engines.

**i-Sint Race 4AM** is recommended for supercharged, turbocharged and naturally aspirated competition engines utilizing racing gasoline, diesel fuel, methanol or nitromethane fuels. **Specifically designed for competition engines.**

**i-Sint Race 4AM** also provides excellent protection in high-performance motorcycles and ATVs.

### TYPICAL CHARACTERISTICS

Viscosity Grade	15W-40	20W-50
Viscosity @ 100° C, cSt	15.3	20.5
Viscosity @ 40° C, cSt	111	172.0
Viscosity Index (Min.)	148	135
Flash Point °F	425	464
Pour Point °F	-25	-17
Gravity, Degrees API	32.0	28.3
Phosphorus, ppm	1200	1200
Zinc, ppm	1300	1300

### AVAILABLE PACKAGING: Totes, Drums, Pails

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.