

eni i-Sint XL 4AM



i-Sint XL 4AM synthetic engine oils are specially formulated to provide superior performance benefits over conventional engine oils. These oils are formulated to provide excellent oxidation stability for long product life, superior low-temperature properties to ensure protection during cold starts, lower volatility for reduced oil consumption, and excellent resistance to viscosity breakdown over conventional engine oils.

i-Sint XL 4AM engine oils meet the most demanding lubrication requirements of today's naturally aspirated, turbocharged and supercharged gasoline fueled and flex-fueled engines. These oils exceed the requirements of API SN, ILSAC GF-5 and are "Resource Conserving" for improved fuel economy.

TYPICAL CHARACTERISTICS

SAE GRADE	0W-20	5W-20	5W-30
Viscosity @ 40 °C, cSt	43.5	44.0	62.0
Viscosity @ 100 °C, cSt	8.3	8.3	11.0
Viscosity Index (Min.)	170	165	165
Pour Point, °C	-45	-45	-45
CCS, cP @ °C	5250 @-35°C	4100 @-30°C	5000 @-30°C
NOACK, wt%	13	12.5	11
HTHS @ 150 °C Viscosity, cP	2.6	2.6	3.0
Zinc, wt%	0.085	0.085	0.085
Phosphorus, wt%	0.077	0.077	0.077

Performance Levels:

- API SN
- ILSAC GF-5
- Resource Conserving

AVAILABLE PACKAGING: Bulk, Totes, Drums, Pails, Cases

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.