

eni i-Sigma 4AM



i-Sigma 4AM is formulated to provide outstanding protection against wear, deposits and high temperature thickening for diesel engines in heavy duty service.

i-Sigma 4AM is recommended for use in pre-2007 model year EGR equipped, four-stroke diesel engines and equipment where the following specifications are referenced or called for:

TYPICAL CHARACTERISTICS

SAE GRADE			15W-40
Viscosity @ 40 °C	D445	cSt	115.8
Viscosity @ 100 °C	D445	cSt	15.7
Viscosity Index	D2270		140
CCS Viscosity	D5293	cP	6500 @-20° C
Pour Point	D97	°C	-33
Flash Point	D92	°C	230
Evaporative Loss, NOACK, wt%	D5800		<15
Specific Gravity 15 °C	D4052		0.873
TBN	D2896		9

SPECIFICATIONS AND APPROVALS

- API CI-4,CH-4,CF/SL
- ACEA A3/B3; E2
- Mack EO-M Plus
- Cummins CES 20078
- Volvo VDS/VDS-2
- Ford M2C171-D
- Caterpillar ECF-1
- Caterpillar TO-2
- Allison C-3/C-4

AVAILABLE PACKAGING: Bulk, Totes, Drums, Pails

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.