



# eni i-Sigma 4AM

**i-Sigma 4AM** mono-grade engine oils are high performance lubricants formulated for use in both on and off highway diesel engines, gasoline engines, and equipment where a mono-grade motor oil is recommended.

**i-Sigma 4AM** mono-grade engine oils are formulated to provide excellent performance in the areas of dispersancy, detergency, wear protection, high temperature thickening, bearing corrosion, and friction control for powershift transmissions.

### TYPICAL CHARACTERISTICS

SAE Viscosity Grade	20W-20	30	40	50
Viscosity @ 40° C, cSt	54.10	86.48	128.22	214.64
Viscosity @ 100° C, cSt	8.52	11.21	14.78	20.44
Viscosity Index	132	117	117	113
Pour Point °F	-25	-15	-5	0
Flash Point °F	392	410	410	465
Specific Gravity @ 60°F	0.8633	0.8783	0.880	0.8844
TBN (ASTM D-2896)	7.3	10	7.3	7.3
Sulfated Ash %	0.88	1.2	0.88	0.88

#### Performance Level:

- SAE 20W-20                      API CF
- SAE 30                             API CF-2, CF/SL
- SAE 40/50                        API CF-2, CF

#### AVAILABLE PACKAGING: Bulk, Totes, Drums, Pails

Due to continual research and development, the information contained herein is subject to change without notice. Always follow manufacturers' recommendations for lubricant performance, viscosity grade and oil change interval as these may vary depending on ambient temperature, fuel composition, model year and environment of operation.